

HI-5115

Features

1/3" SONY CCD Color Camera
 520 TV line 0.1 Lux/F2.0
 LED 20 unit 0 Lux 15M IR On
 Auto White Balance , AES
 Lens Fix 4 mm. Day& Night
 Power DC 12V / 120mA & 180mA



Specification

Image Device	1/3" Sony CCD sensor
Scanning Frequency	NTSC:15,734KHz(H), 60Hz(V);PAL: 15,625KHz(H),50Hz(V)
Scanning System	NTSC: 525 line 2:1 interlace PAL:625 lines 2:1 interlace
Effective Pixels	NTSC: 512(H) x 492(V); PAL:512(H) x 582(V)
Electronic Shutter	N:1/60- 1/100,000sec (Auto);P:1/50-1/100,000sec (Auto)
Horizontal	520 TV lines
White-balance	Auto white balance (2500 °K~9500 °k)
Synchronizing System	Internal
Sensitivity	0.1 Lux , 0 Lux at IR on / F2.0
BLC	Auto
Signal to Noise	More than 48dB (AGC off)
IR Distance	15 Meters (Based on: object of view reflected IR light)
IR LED	High Light LED x 20 pcs
IR Status	500
IR View Angle	View angle: 70 °, Beam spread: 40 °/per LED
IR Wavelength	850nm +- 25nm
LED Life	More than 10,000 hours
Lens	4 mm Standard (4,8,12,16mm option)
Power Consumption	IR on: 180mA, IR off: 120mA (DC 12V) +- 5mA
Power Supply	DC 12V
Temperature	Operating: -10 to 50 °C
Video Output	Composite 1.0 Vp-p at 75 ohm
Construction	PVC Design
Dimensions	115(W) x 75(H)
Weight	0.150kg